

### wood



Nature at your feet

#### Amorim Revestimentos S.A

Rua do Ribeirinho 202 P. O. Box 13 4536-907 S. Paio de Oleiros PORTUGAL

p\_(+351) 227 475 600 e\_wicanders.ar@amorim.com www.wicanders.com





Wicanders has a legacy that goes back to 1868 and is the global leading brand in flooring products with cork technology. Present in more than 70 countries,

in flooring products with cork technology. Present in more than 70 countries, its promise is to provide Floors for Living, ready for real life, for our home and office, for our different rhythms, for our family and pets, for all those wonderful and simple, yet sometimes unexpected moments. Floors for our lives.

Over the years, Wicanders has developed sustainable floor and wall coverings with exclusive properties due to its innovative Corktech technology. By combining state of the art technology with the exclusive natural properties of cork, a higher standard in flooring is achieved. Available with cork, wood and stone looks, its products are al to provide a silent and thermally insulated environment, that endures impacts and is very comfortable to walk and stand on.

Wicanders means wellbeing, a choice for life!









#### FROM NATURE, TO YOUR SPECIAL SPACE.

Technology only makes sense if it improves people's lives. This concept finds expression in products developed with Corktech technology.

By using a unique engineered multilayer structure, which combines state of the art technology with the exclusive natural properties of cork, a higher standard in flooring is achieved, providing the perfect match between design and wellbeing.

Wicanders uniqueness is daily achieved by continuously research on how end customers think and live their spaces. Wicanders brings to the market products that provide a silent and thermally insulated environment, that endures through time and are sustainable at the same time.





Walking Comfort



Silence

Impact Resistance



GET THE BEST RESULTS WITH WICANDERS ACCESSORIES!	50
CREATED BY HUMANS, INSPIRED BY NATURE	52
CORK – A SUSTAINABLE RAW MATERIAL	53
PRODUCT SELECTOR	54
WICANDERS' RANGE	59

Sample images are cut from larger pieces. Decor and shade may vary slightly.









Blonde Oak BON1001 1220 x 185 x 10,5mm



European Oak B0Q2004 1220 x 185 x 10,5mm





### **Tradition** Keeping your comfort is our tradition.

Flooring is one of the most important structural decisions when decorating a space from scratch or remodeling one. The hue and style you choose for the floor of your space sets the tone for the ambiance to be built and it's always an extension of you and your style.

These 6 golden wood visuals are the Traditional approach that will go along with different types of furniture and will not overstep the overall decoration.

The bedroom is a space where you can have inner time and relax before each morning's rush. The comfort of your bed is crucial as is also the pleasant touch of walking barefoot on the floor - that's what Wicanders products can provide: beauty and thermal comfort.







#### Savanna Limed Oak BON6001

1220 x 185 x 10,5mm





Amber Cherry B0Q7003 1220 x 185 x 10,5mm

Light Sucupira B009001 1220 x 185 x 10,5mm



#### White Oak BOM8001 1220 x 185 x 10,5mm



Frozen Oak BON9001 1220 x 185 x 10,5mm

#### Nordic

# Innovation always finds original ways of expression.

1 1 2 2 2 2 2 2

Nordic-colour flooring visuals have the power to impact ambiances in a contemporary way. You may change the decor over time and the gentleness and lightness effect provided by the flooring will remain.

Whether it's a light or dark grey flooring in a minimalist and functional decor that characterizes the scandinavian style, these spaces can be highly personalized and welcoming.









Platinum Oak BOM6001 1220 x 185 x 10,5mm



Storm Oak BON3001 1220 x 185 x 10,5mm



Brume Oak BON8001 1220 x 185 x 10,5mm







Midnight Oak BOM5001 1220 x 185 x 10,5mm

Quartz Larch BOW3001 1220 x 185 x 10,5mm





Ivory Salt Oak BON2001 1220 x 185 x 10,5mm Alaska Oak B0Q0003 1220 x 185 x 10,5mm



Croft Oak B0V9001 1220 x 185 x 10,5mm



Chalk Oak B0Q1003 1220 x 185 x 10,5mm



Indian Dark Oak B0S5001 1220 x 185 x 10,5mm



Bark Oak BOV8001 1220 x 185 x 10,5mm







#### Cottage

To drive the look home in your living room, opt for a Cottage look flooring and for one statement-making element to finish off the space and become the focal point of the room.



Old Larch BOW6001 1220 x 185 x 10,5mm







Polar Nature Oak BOR9001 1220 x 185 x 10,5mm



Oiled Taupe Oak BOWA001 1220 x 185 x 10,5mm



Provence Oak B0Q3003 1220 x 185 x 10,5mm



Fall Pine B050001 1220 x 185 x 10,5mm



Highland Pine BOS1001 1220 x 185 x 10,5mm wood Go

#### Reclaimed

These three exciting flooring looks result from the combination of life's soul with contemporary novelty.

Enjoy them to the fullest by mixing industrial, time-worn, and contemporary decor elements. Your living room will achieve an exciting variety as well as a cohesive flair that unifies the Reclaimed style.





Shell Oak B0N4001 1220 x 185 x 10,5mm









#### Limed White Rustic Oak BOWB001 1220 x 185 x 10,5mm



Rustic Taupe Oak BOWCOO1 1220 x 185 x 10,5mm

# Technical solution

PROTECTIVE WEAR LAYER

HIGH RESOLUTION DECORATIVE

SOLID VINYL LAYER

AGGLOMERATED CORK 1,5MM

HDF - HIGH DENSITY FIBERBOARD WITH CORKLOC

INTEGRATED CORK UNDERLAY 1,2MM

# Finishing & Warranty



Suitable for Heavy Traffic Residential areas and Moderate Traffic Commercial areas.





Suitable for Heavy Traffic Residential areas and Medium Traffic Commercial areas.







# **wood** Essence

#### Formats

1220 x 185 x 10,5mm <sup>48 x 7 1/4 x 3/8"</sup>

1830 x 185 x 11,5mm <sup>72 x 7 1/4 x 1/2</sup>" Floating

RANGE	Go	23 31	<b>i</b> \$
	Essence	23	
	Resist	23	
	Resist+	23	•
	Hydrocork		Ŷ
Heavy Traffic Residential areas			
32	Medium Traffic Commercial areas	Heavy Traffic Cor	nmercial areas
\$ Budget products		Extra Cork	Waterproof







Prime Desert Oak D8F5001 1830 x 185 x 11,5mm

#### Classic Prime Oak D8F4001 1830 x 185 x 11,5mm



Golden Prime Oak D8F7001 1830 x 185 x 11,5mm



Prime Rustic Oak D884002 1220 x 185 x 10,5mm D884001 1830 x 185 x 11,5mm



Country Prime Oak D8F8001 1830 x 185 x 11,5mm



Prime European Cherry D826003

1220 x 185 x 10,5mm



## Tradition Turning dreams into reality.

Flooring has the ability to create or change the mood of every space. Depending on the style that you want to create throughout your home, you can choose between flooring looks that will totally impact the overall style or the ones that will turn the furniture set in a more low profile approach.

A living room is the social area of a home and it needs to be both a casual and a formal space that will act as a comfortable space to enjoy family time or to host a special event.

Flooring visuals with a Tradition look like these 8, offer the perfect complement to your furniture providing a sophisticated ambiance.



Dapple Oak D8F1001 1830 x 185 x 11,5mm



Ivory Chalk Oak D887001 1220 x 185 x 10,5mm D887002 1830 x 185 x 11,5mm

Ivory Chalk Oak

#### Nordic

When going for a soothing and luminous ambiance, go with the Nordic style!

Wake up your bedroom with adorable pastel colours combined with a floor in a soothing colour palette of grays and the result will be a gorgeous bedroom prepared to greet you every night and morning. Splashes of colour will definitely be a great addition!



Prime Arctic Oak D8F6001

1830 x 185 x 11,5mm















Nebula Oak D8F3001 1830 x 185 x 11,5mm



Coal Oak D8F2001 1830 x 185 x 11,5mm



Inspired Pine D898001 1220 x 185 x 10,5mm



#### Cottage

When aiming to build your living room with an impactful decor identity filled with an overall neutral palette, choose one of these 7 charming looks and embrace a cohesive Cottage style by adding some nature inspired elements with rustic wood furniture.



Washed Haze Oak D8G2001 1830 x 185 x 11.5mm





Washed Arcaine Oak Washed Highland Oak D8G3001 D8G1001 1830 x 185 x 11.5mm 1830 x 185 x 11.5mm





Nebraska Rustic Pine Washed Castle Oak D885001 1220 x 185 x 10,5mm D8G4001

D885002 1830 x 185 x 11,5mm

1830 x 185 x 11,5mm





Rustic Eloquent Oak D8F9001

1830 x 185 x 11,5mm



## Reclaimed Exceeding expectations is an art form.

If you prefer to use flooring as the main focal point of your room, consider the rich tones and presence of these Reclaimed looks - ideal backgrounds to create a bold and strong atmosphere.

Striking textures of wood can be coordinated with a splash of bold colour in order to build up a powerful ambiance filled with details.

Reclaimed flooring and furniture are mirrors of history, able to enrich each space in a unique, craftsman way.







Glacier Rustic Pine D822003 1220 x 185 x 10,5mm



Sorrel Carve Oak D838003 1220 x 185 x 10,5mm D838004 1830 x 185 x 11,5mm

# Technical solution

PROTECTIVE WEAR LAYER

HIGH RESOLUTION IMAGE

AGGLOMERATED CORK 3,2MM

HDF – HIGH DENSITY FIBERBOARD WITH CORKLOC

INTEGRATED CORK UNDERLAY 1,2MM

# Finishing & Warranty



NPC surface finish (Natural Power Coat) is the last innovation in varnished cork floors being suitable for the most demanding domestic areas and commercial areas with moderate traffic, achieving a class of 32 (ISO 10874) and AC6 (EN 13329). Due to its chemical reaction during the hot coating process it is extremely wear resistant and highly flexible. This green coat also has a very pleasant haptic, which emphasizes the warmth and natural structure of cork.







#### Tradition

Light, vivid, and dry brown, are and always will be, timeless wood colours that can be placed in a wide variety of spaces and as a rich complement to diverse styles.



Linen Cherry BOR0001 1220 x 185 x 10,5mm



Light Beech BOTO002 1220 x 185 x 10,5mm



Wheat Pine BOR3001 1220 x 185 x 10,5mm



Sand Oak BOR1001 1220 x 185 x 10,5mm



Castle Raffia Oak BOPOOO1 1220 x 185 x 10,5mm



Castle Toast Oak BOP1001 1220 x 185 x 10,5mm



Nature Oak BOT5001

1220 x 185 x 10,5mm





Elegant Oak BOR4001 1220 x 185 x 10,5mm

#### Nordic

When choosing the perfect hue and look of flooring for your special space, you will consider if it matches your personal style in a timeless manner, and also if it will endure the test of time.

Your bedroom will be the perfect hideaway to the busy day-to-day life with a design and serene atmosphere.



Limed Grey Oak B0T7001 1220 x 185 x 10,5mm



Claw Silver Oak BOV3001 1220 x 185 x 10,5mm





Rustic Limed Gray Oak

BOUOOO1 1220 x 185 x 10,5mm



Cinder Oak BOR7001 1220 x 185 x 10,5mm





Arcadian Soya Pine BOP4001 1220 x 185 x 10,5mm

#### Arcadian Rye Pine BOP5001 1220 x 185 x 10,5mm



Century Fawn Pine BOP7001 1220 x 185 x 10,5mm

#### Cottage

In a cottage home style kitchen, you can focus more on individual pieces, and less on cohesive flow.

Embrace contrast by hanging an industrial lamp above a wooden breakfast table to add charisma.









1220 x 185 x 10,5mm







Nordic Ash B0V4001 1220 x 185 x 10,5mm





Sawn Twine Oak BOP2001 1220 x 185 x 10,5mm

#### Reclaimed

The strong warm colour variation and rich texture of these 3 Reclaimed looks are the perfect match to balance clean and light workspace furniture.

Sawn Twine Oak

# Technical solution

PROTECTIVE WEAR LAYER

HIGH RESOLUTION DECORATIVE

SOLID VINYL LAYER

AGGLOMERATED CORK 1,5MM

HDF - HIGH DENSITY FIBERBOARD WITH CORKLOC

INTEGRATED CORK UNDERLAY 1,2MM

# Finishing & Warranty



Suitable for Heavy Traffic Residential areas and Heavy Traffic Commercial areas.















#### Tradition

Traditional golden wooden flooring looks combined with the exclusive natural properties of cork are the perfect features to place in a nursery and create an ambiance rich in beauty and wellbeing.

#### White Washed Oak E1XH001 1220 x 185 x 10,5mm

#### Elegant Light Oak E1XG001 1220 x 185 x 10,5mm

#### Elegant Oak E1R4001 1220 x 185 x 10,5mm

# Elegant Dark Oak

1220 x 185 x 10,5mm



Sand Oak E1R1001 1220 x 185 x 10,5mm









Antique Frozen Pine Claw Silver Oak E1XD001 1220 x 185 x 10,5mm

### E1V3001 1220 x 185 x 10,5mm



Frozen Oak E1N9001 1220 x 185 x 10,5mm



Cinder Oak E1R7001 1220 x 185 x 10,5mm

#### Nordic

Light tone flooring and clean lines furniture will always appear to amplify spaces.









Light Washed Oak E1X1001 1220 x 185 x 10,5mm

#### Limed Grey Oak E1T7001 1220 x 185 x 10,5mm



Grey Washed Oak E1XK001

1220 x 185 x 10,5mm



Dark Grey Washed Oak

1220 x 185 x 10,5mm





Equip your office with a contemporary rustic beauty and functionality. Pick your favourite earthy hue and wood texture and enjoy the silence and impact resistance that Wicanders products provide.

These genuine nature-infused Cottage looks will layer up your working space with organic warmth that feels both fresh and real, light and grounded.

Clean-cut furniture and daily-office objects are all you need to embrace the full design concept and maintain a balanced contemporary Cottage style.





Chalk Oak E1Q1001 1220 x 185 x 10,5mm

#### European Nature Oak E1XE001 1220 x 185 x 10,5mm





Provence Oak E1Q3001 1220 x 185 x 10,5mm



#### Smoked Rustic Oak E1U4001 1220 x 185 x 10.5mm

Alaska Oak E1Q0001 1220 x 185 x 10,5mm





#### Antique Washed Pine E1XC001 1220 x 185 x 10,5mm

Bleached Oak E1X0001 1220 x 185 x 10,5mm



#### Antique Smoked Pine E1XB001 1220 x 185 x 10,5mm



European Smoked Oak E1L7001 1220 x 185 x 10,5mm





#### Reclaimed

The Reclaimed style is a lasting interior design trend characterized by design with a story to tell - from flooring, furniture, to other decor elements, all convey a fresh message of time passed.





Oiled Nature Oak E1XN001 1220 x 185 x 10,5mm







Dark English Oak E1XM001 1220 x 185 x 10,5mm



Grey Rustic Pine E1W2001 1220 x 185 x 10,5mm



Nature Rustic Pine E1XA001 1220 x 185 x 10.5mm

Brown Rustic Pine E1W1001 1220 x 185 x 10,5mm

# Technical solution

PROTECTIVE WEAR LAYER

HIGH RESOLUTION DECORATIVE

AGGLOMERATED CORK 2,7MM

HDF - HIGH DENSITY FIBERBOARD WITH CORKLOC

INTEGRATED CORK UNDERLAY 1,2MM

# Finishing & Warranty



HPS surface finish (High Performance Surface) has been specially developed for areas with heavy traffic, such as commercial, business or general public areas. This high performance surface has an extra hard wearing surface combined with Nano-Beads Technology, where extremely tiny beads are embedded in a top layer for improved properties such as scratch, slip, scuff and stain resistance.







36




# **NO PROBLEM.** IT'S HYDROCORK.

hydre cork READY FOR REAL LIFE

# DURABLE, RESISTANT AND EASY TO MAINTAIN



100% WATERPROOF



# **EASY** AND **FAST** INSTALLATION

### STABLE AND STRONG INSTALLATION WITH **COMPRESSION SYSTEM**

PressFit is a revolutionary compression system that takes full advantage of the amazing cork properties - flexibility, elasticity and compressibility - functioning like a cork stopper



### **REDUCED** INSTALLATION COSTS

Hydrocork is only 6mm thick making it easy to cut. Avoids the need to remove the existing skirtings or to cut doors and it can be installed on top of other flooring materials.





\* Please see the terms and conditions of Wicanders Limited Warranty in the website.

Promotes global sustainability, environmental health, and safety.





Castle Raffia Oak \*B5P0001 1225 x 145 x 6mm



Nature Oak \*B5T5001 1225 x 145 x 6mm



European Oak

\*B5Q2001

1225 x 145 x 6mm

Castle Toast Oak \*B5P1001 1225 x 145 x 6mm

### Tradition No problem. It's ready for real life.

With Hydrocork, you no longer need to be worried if the flooring is able to endure the test of time in a gracious way and how it resists impacts. You don't even need to fear over daily spillings due to its waterproof endurance.



Elegant Oak \*B5R4001

1225 x 145 x 6mm







Linen Cherry \*B5R0001 1225 x 145 x 6mm





Sand Oak \*B5R1001 1225 x 145 x 6mm



B5WR001 1225 x 195 x 6mm





### Wheat Pine \*B5R3001 1225 x 145 x 6mm

### Nordic

This style is characterized by simple yet rich decor elements. Mixing different clean cut chairs can be the fun approach that will help to provide life without loosing the functionality that is part of the Nordic design.



Claw Silver Oak \*B5V3001 1225 x 145 x 6mm



### Limed Grey Oak \*B5T7001 1225 x 145 x 6mm

### Cottage

Flooring can either be the focal point of a room, or a background that aggregates other design elements. It's important to have a clear goal in each new design project in order to guarantee a consistent layout. When you've that figured out, it's with ease that you'll be able to extend your personality into your special space.



Cinder Oak \*B5R7001 1225 x 145 x 6mm



### Arcadian Artic Pine B5WT001 1225 x 195 x 6mm





Alaska Oak \*B5Q0001 1225 x 145 x 6mm







Arcadian Soya Pine \*B5P4001 1225 x 145 x 6mm

### Arcadian Rye Pine \*B5P5001 1225 x 145 x 6mm





Century Fawn Pine \*B5P7001 1225 x 145 x 6mm

### Century Morocco Pine \*B5P6001 1225 x 145 x 6mm



Chalk Oak \*B5Q1001 1225 x 145 x 6mm



Rustic Fawn Oak B5WU001 1225 x 195 x 6mm



Light Dawn Oak B5WS001 1225 x 195 x 6mm



B5WV001

1225 x 195 x 6mm







Sylvan Gold Oak B5L8001 1225 x 195 x 6mm

### Sylvan Brown Oak <sup>B5WQ001</sup>

1225 x 195 x 6mm



### Sawn Bisque Oak \*B5P3001

1225 x 145 x 6mm



Sawn Twine Oak \*B5P2001

1225 x 145 x 6mm



# Technical solution

PROTECTIVE WEAR LAYER

HIGH RESOLUTION DECORATIVE

SOLID VINYL LAYER

AGGLOMERATED CORK COMPOSITE CORE WITH PRESSFIT 3MM

BALANCING VINYL LAYER

# Finishing & Warranty



Suitable for Heavy Traffic Residential areas and Heavy Traffic Commercial areas.



\*Please see the terms and conditions of Wicanders Limited Warranty on the website.

### Technical Data Sheet

			GO		ESSEN	ICE	
				FLOATING			
		0,2mm Wear Layer   0,3mm Wear Layer 1220 x 185 x 10,5mm   48 x 71/4 x 3/8"			NP4 1830 x 185 x 11,5m 1220 x 185 x 10,5m	<b>m</b>   72x71/4x1/2"	
_evel of use Domestic	ISO 10874	Class	23	ISO 10874	Class	23	ISO 10874
evel of use Commercial	ISO 10874	Class	31/32	ISO 10874	Class	32	ISO 10874
Surface Finishing	-	-	-	-	-	Polyutherane moisture-curing	-
Vear Layer binder content	-	-	-	-	-	-	-
	Standard- Test Method	Unit	Specification	Standard-Test Method	Unit	Specification	Standard-Test
Seneral properties							Method
Dimensions: Width .ength	ISO 24342	mm	± 0,10 up to max. 0,5 max. 2,0	ISO 24342	% mm	± 0,10 with max. 0,5 max. 2,0	ISO 24342
Nominal thickness for cork surfaces	-	-	-	-	-	-	-
Overall thickness	ISO 24346	mm	± 0,25	ISO 24346	Average mm Individual values mm	Maximum deviation from the average ± 0,30	ISO 24346
quareness straightness measured at the surface layer	ISO 24342	mm	″≤ 0,50 ≤ 0,30″	ISO 24342	mm	≤ 0,50 ≤ 0,30	ISO 24342
Apparent density Average ndividual values	EN 672	Kg/m³	, - Nominal (930) ± 50	EN 672	Kg/m³	≥ 760 ≥ 95% nominal value	EN 672
1ass per unit area	ISO 23997	g/m²	Nominal +13% / -10%	ISO 23997	g/m²	8000-/+10%	ISO 23997
imensional stability (humidity)	EN 669 (Annex C)	mm	≤5	-	-	-	EN 669 (Annex C)
imensional stability (heat)	EN 14085 Annex C/ EN 669	%	-	EN 14085 Annex C / EN 669	%	≤5	EN 14085 Annex C/ EN 669
)penings between panels werage ndividual values	EN 14085 (Annex B)	mm	″ ≤ 0,15 ≤ 0,20″	EN 14085 Annex B	mm	≤0,15 ≤0,20	EN 14085 (Annex B)
eight difference between panels verage ıdividual values"	EN 14085 (Annex B)	mm	- ≤ 0,20	EN 14085 Annex B	mm	≤ 0,15 ≤ 0,20	EN 14085 (Annex B)
latness of the panel ength: concave / convex /idth: concave / convex″	EN 14085 (Annex A)	%	≤ 0,50 / ≤1,0 ≤ 0,10 / ≤ 0,15	EN 14085 Annex A	%	≤ 0,50 / ≤1,0 ≤ 0,10 / ≤ 0,15	EN 14085 (Annex A)
hickness of top cork surface	-	-	-	ISO 24346	mm	≥3	-
esidual indentation	ISO 24343-1	mm	≤ 0,15	ISO 24343-1	mm	≤ 0,3	ISO 24343-1
olour fastness	ISO 105-BO2	Blue wool scale	≥6	-	-	-	ISO 105-BO2
leel resistance N/50 mm werage ndividual values	-	-	-	ISO 24345	N/50 mm	0	-
Vearing group	-	-	-	-	-	-	-
lassification properties							
/earing Group	EN 660-1	Thickness loos ( Imm)	-	-	_	-	EN 660-1
)veral thickness	ISO 24346	mm	-	-	-	-	ISO 24346
hickness of wear layer	ISO 24340	mm	0,2	-	-	-	ISO 24340
astor chair class	-	-	-	EN 425	Visual effect after 25 000 cycles	No disturbance to the surface other than slight change in appearance and no delaminating shall occur	EN 425
imulated movement of a furniture leg	EN 424	Visual effect	No damage shall be visible after testing with a type 2 foot	EN 424	Visual effect	No damage shall be visible when tested with foot type 2	EN 424
hickness swelling floor panel	-	-	-	ISO 24336	%	≤18	-
afety properties							
ire resistance	EN 13501-1	Class	Bfl s1	EN13501-1	Class	Cfl s1	EN 13501-1

RESIST			RESIST+			HYDROCO	) PK
KE3131	FLO	ATING	KESIST+			LOW THICKNESS	
0,55mm Wear L 1220 x 185 x 10,5mm   4	.ayer		0,55mm Wear Lay 1220 x 185 x 10,5mm	<b>rer   HPS</b> 48×71/4×3/8°		0,55mm Wea 1225 x 145 x 6mm   48 1225 x 195 x 6mm   48 605 x 145 x 6mm   23	r Layer 7/32×511/16×1/4″ 7/32×711/16×1/4″
Class	23	ISO 10874	Class	23	ISO 10874	Class	23
Class	33	ISO 10874	Class	33	ISO 10874	Class	33
-	-	-	-	-	-	-	-
-	-	ISSO 10582	-	TYPEI	-	-	-
Unit	Specification	Standard-Test Method	Unit	Specification	Standard-Test Method	Unit	Specification
mm	± 0,10% up to max. 0,5 max. 2,0	-	-	-	ISO 24342	mm	± 0,10% up to max. 0,5 max. 2,0
-	-	ISO 24342	mm	2,7	-	-	-
mm	± 0,25	-	-	-	ISO 24346	mm	nominal ± 0,25
	≤0.50 ≤0.30	ISO 24342	mm	≤ 0,20 ≤ 0,30	ISO 24342	mm	≤ 0,50 ≤ 0,30
Kg/m³	- Nominal value (960) ± 50	-	-	-	-	-	-
	Nominal value (10150) - 10 % + 13%	ISO 23997	g/m²	Nominal value (9210) - 10 % + 13%	ISO 23997	g/m2	Nominal +13% / -10%
mm	≤5	-	-	-	EN 14085 Annex C/ EN 669	mm	≤5
%	-	-	-	-	ISO 23999	%	≤ 0,25
mm	- ≤ 0,20	EN14085 Annex C	%	- ≤0,25	EN 14085 (Annex B)	mm	≤ 0,20
mm	- ≤ 0,20	EN 14085 (Annex B)	mm	- ≤ 0,15	EN 14085 (Annex B)	mm	≤0,20
	≤ 0,50 /≤ 1,0 ≤ 0,10 /≤ 0,15	EN 14085 (Annex A)	%	≤ 0,50 /≤ 1,0 ≤ 0,10 /≤ 0,15	EN 14085 (Annex A)	%	≤ 0,50 / ≤ 1,0 ≤ 0,10 / ≤ 0,15
-	-	-	-	-	-	-	-
mm	≤ 0,15	ISO 24343-1	mm	≤ 0,10	ISO 24343-1	mm	≤ 0,1
Blue wool scale	≥6	ISO 105-BO2 Method	Blue wool scale	≥6	ISO 105-BO2	Blue wool scale	≥6
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
Thickness loos ( Imm)	Wear group T	-	-	-	-	-	-
mm	≥ 3,0	-	-	-	-	-	-
mm	≥ 0,55	-	-	-	ISO 24340	mm	0,55
Visual effect - after 25 000 cycles	No disturbance to the surface other than slight change in appearance and no delamination shall occur	ISO 4918	Visual effect	No disturbance to the surface other than slight change in appearance and no delamination shall occur	EN 425	Visual effect - after 25.000 cycles	No disturbance to the surface other than a slight change in appearance and no delamination shall occur
Visual effect	No damage shall be visible after testing with a type 2 foot	ISO 16581	Visual effect	No damage shall be visible when tested with foot type 0	EN 424	Visual effect	No damage shall be visible after testing with a type O foot
-	-	ISO 24336	%	≤15	ISO 24336	%	≤15
Class	Bfl s1	EN 13501-1	Class	Bfl s1	ISO 11925-2/ISO 9239-1 (classification according to EN 13501-1)	Class	Bfl-s1

### Technical Data Sheet

			GO	ESSENCE				
			F	FLOATING	LOATING			
	0,2mm Wear Layer   0,3mm Wear Layer 1220 x 185 x 10,5mm   48 x 71/4 x 3/5"			NPC 1830 x 185 x 11,5mm   72 x 7 1/4 x 1/2" 1220 x 185 x 10,5mm   48 x 71/4 x 3/8"				
Slip classification	EN 13893	Class	DS	EN 13893	Class	DS	EN 13893	
Formaldehyde emission	DIN EN 717-1	Class	E1	DIN EN 717-1	Class	E1	DIN EN 717-1	
Electrical behaviour	EN 1815	KV	Antistatic	EN 1815	KV	Not Antistatic	EN 1815	
Content pentachlorophenol (PCP)	CEN/TR 14823 (ihd-W 409) EN 14041 Annex B	mg/Kg %	- Undetectable	CEN/TR 14823 (ihd-W 409)	mg/Kg	PCP Free	CEN/TR 14823 (ihd-W 409) EN 14041 Annex B	
Additional properties								
Stains resistance	ISO 26987 (a)	Grade	Grade 0 (b) lodine Grade 2 (b)	EN 438 (c) ISO 26987 (a)	Grade Grade	Grade 0 = unchanged (b)	ISO 26987 (a)	
Thermal resistance	EN 12667	(m²K)/W	R≤0,15	EN 12667	(m²K)/W	R≤0.15 (m²K)/W (d)	EN 12667	
Impact sound reduction	ISO 140-8	dB ( <b>A</b> Lw)	16	ISO 140-8	dB ( <b>A</b> Lw)	18	ISO 140-8	
Walking noise	IHD - W431	dB (A)	Reduction improvement 11,4 dB (A) Difference of loudness 45,4%	IHD - w431	dB (A)	Reduction improvement 12dB Difference of loudness 47,5%	IHD - W431	
"Reflected walking noise Improved measure Difference of loudness [Sone] relative difference"	-	-	-	-	-	-	-	
Light fastness	-	-	-	ISO 105-B02 EN 15187	Blue wool scale Blue wool scale	>6	-	
Abrasion resistance 1	-	-	-	EN 14354 Annex D	Revolutions Wt	0	-	
Abrasion resistance 2	-	-	-	EN 13329 EN 14354	Class	AC6 WR3	-	
Swelling of the joints (Moisture Exposure)	-	-	-	-	-	-	-	
ASTM Standards								
"Airborne sound Transmission Loss"	-	-	-	-	-	-	-	
Impact sound transmission	-	-	-	-	-	-	-	
Smoke density	-	-	-	-	-	-	-	
Radiant panel (critical radiant flux)	-	-	-	-	-	-	-	
Thermal resistance	-	-	-	-	-	-	-	
Residual indentation	-	-	-	-	-	-	-	
Static load limit	-	-	-	-	-	-	-	
Ignition characteristics of finished textile floor covering systems	-	-	-	-	-	-	-	

- (a) The following products were tested: desinfectant, C2H5OH, NH4OH, ditric acid, iodine, petroleum, spirit.
- (b) Grade 0 Unchanged / Grade 1 Very little change / Grade 2 Little change / Grade 3 Change / Grade 4 Strong Change.
- (c) The following products were tested: acetone, coffee, NaOH, H2O2 at 3%, black shoe cream.
- (d) Suitable for floor heating systems , according to German Federal Association Radiant Panel Heating.

Wicanders Flooring Collection is supported by a warranty. Please, read the warranty terms on **www.wicanders.com** 



WRT | PU

Greenguard Certification helps the identification of interior products and materials that have low chemical emissions, improving the quality of the air in which the products are used. It promotes global sustainability, environmental health, and safety.



WRT | PU | SANDED

TÜV-PROFICERT-product Interior brand is a voluntary, independent label for VOC-emission and quality of floorings. The results comply with the emission thresholds of AgBB, Belgian VOC regulation, Finnish M1 classification, BREEAM Exemplary Level, LEED v4 (outside North America), RAL-UZ 120 and Austrian Eco Label (Guideline UZ 56).

RES	IST		I	RESIST+		HYDR	OCORK
		FLOATING				LOW THICKN	ESS FLOATING
0,55mm W 1220 x 185 x 10,5r	<b>∕ear Layer</b> nm   48×71/4×3/8″			Wear Layer   HPS 0,5mm   48x71/4x3/8*		1225 x 145 x 6mm	Wear Layer   487/32x511/16x1/4"   487/32x711/16x1/4"   2313/16x511/16x1/4"
Class	DS	EN 13893	Class	DS	EN13893	Class	DS
Class	E1	EN 717-1	Class	E1	DIN EN 717-1	Class	E1
kV	Antistatic				-	-	-
mg/Kg %	PCP free	EN 14041 Annex B	%	PCP Free	EN 14041 Annex B	%	Undetectable
Grade	Grade 0 (b) Iodine Grade 2 (b)	-	-	-	ISO 26987 (a)	Grade	Grade 0 (b) Iodine grade 2 (b)
(m²K)/W	0,093	EN 12667	(m²K)/W	≤ 0,11	EN 12667	(m2K)/W	0,05
dB ( <b>A</b> Lw)	16	EN ISO 10140-3:2010	dB (Lw)	17	ISO 140-8	dB (Lw)	16 dB
dB (A)	Reduction improvement 11,4 dB(A) Difference of loudness 45,4%	-	-	-	IHD -W431	dB (A)	Reduction improvement 11,1dB Difference of loudness 51,1%
-	-	IHD - W - 431	dB (A) %	9,5 49	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	IHD 423	mm	No visible effect
-	-	-	-	-	ASTM E90 /ASTM E413	STC (dB)	62 dB
-	-	-	-	-	ASTM E492 /ASTM E989 ASTM E2179	IIC (dB) IIC	61 dB 16 dB
-	-	-	-	-	ASTM662	KW/m2	Flaming & non flaming ≤ 450
-	-	-	-	-	ASTM E648	(W/cm2)	≥ 0,45 W/cm2 Exceeds, Class I
-	-	-	-	-	ASTM C177	R-value (m2K)/W	0,0432
-	-	-	-	-	ASTM F1914	%	0,40%
-	-	-	-	-	ASTM F970	in or mm	0,005 in (load of 250 lb) 0,127 mm (load of 113.4 Kg)
-	-	-	-	-	ASTM D2859	-	Meets the criteria



WRT|PU

As of January 2012, France has adopted regulations that limit total VOC emissions of building products. Manufacturers, selling their products in France must obtain a classification ranging from A+ (very low emissions) to C (high emissions). The declared goal is to improve indoor air quality in private/ commercial buildings.



An Environmental Product Declaration is a verified document that reports environmental data of products based on life cycle assessment and other relevant information in accordance with the international standard ISO 14025.



WRT | PU | SANDED

The goal of the German Cork Association is to assure the quality of cork products, as well as the optimization of manufacturing processes and the support of research projects.



WRT | PU | SANDED

The Blue Angel is a voluntary certification that guarantees that a product or service meets high standards when it comes to its environmental, health and performance characteristics. In the process, these products and services are always evaluated across their entire life cycle.



Global GreenTagCertTM is an independent certification and rating scheme for green products, recognized by the Green Building Councils of Australia and New Zealand.

This certification also allows the products to be listed in the Ecospecifier Global eco-products.

# Get the best results with Wicanders accessories



#### Underlays Increased comfort and insulation

To reinforce the already amazing insulation properties of cork flooring, Wicanders provides Acousticork, a cork underlay which lets you turn your home into an even cosier space.

Acousticork reduces the walking sound and heat dispersion. Overall, it makes rooms cosier and more peaceful, which is essential in making any house feel like home.

For Hydrocork products, if you wish to use underlay, please consult Wicanders website or your supplier for more information.

- High durability and long term resilience
- Increases floor thermal insulation
- Natural and sustainable product
- Easy to handle and install





#### Maintenance

#### Optimal care for an everlasting beauty

To keep your floor spotless, Wicanders has available a set of auxiliary products. Each of these has a specific purpose and is designed to make the caring of your floor as easy as possible.

### Regular Maintenance



#### Wicanders Soft Cleaner This mild detergent is appropriate for weekly or even daily cleaning. It can be used to remove dirt, stopping it from infiltrating in the joints and in the regular embossing of the product.

#### Wicanders Spray Cleaner

Designed for regular cleaning, this mild detergent has the advantage of being a spray, which makes it a quick and easy solution to apply directly on the floor. It is very effective in cleaning dirt or grease stains.



#### Skirtings

### The perfect match to make a pleasant interior

In order to help create a more classy and harmonious interior, Wicanders provides skirting profiles to complement your floor. Create your ideal transition between the walls and the floor, whether by an exact match or contrasting colours.

Contact your supplier for information on the available skirting references.



### CREATED BY HUMANS, INSPIRED BY NATURE

Wicanders represents an unique balance between the creation of innovative products and the protection of the environment, combining state-of-the-art technology with the amazing natural properties of cork.



**A green production process** – Cork waste resulting from the industrial process is 100% reincorporated into the production, creating an ecologically virtuous cycle.



**Intensive use of biomass** – The cork powder resulting from the industrial process is burned in order to create biomass which is then used as a major source of energy to supply the production facilities, allowing Wicanders also to base its production in a sustainable source of energy.

٥_
<u>م</u> لا
121

Low carbon emission – Cork's natural property of retaining CO<sub>2</sub> combined with an eco-sustainable industrial process allows Wicanders to develop eco-efficient products with a low carbon emissions factor, positively contributing to a sustainable environment.



**Indoor Air Quality** – Refined to be free of harmful phthalates Wicanders products have been awarded with worldwide indoor air quality certifications such as Greenguard Gold or A+.



**Negative Global Warming Potential** - The majority of Wicanders products contribute to reduce global warming, since they retain more CO<sub>2</sub> than they emit.



### **CORK - A SUSTAINABLE RAW MATERIAL**

Cork comes from the bark of the Cork Oak, a slowly growing tree from the Mediterranean basin that may live for 200 years and plays a central role in the social and economic development of this region.

Truly environmental-friendly - The extraction of cork and its related industries are remarkably sustainable, since the tree is never cut or damaged during the extraction process and the bark regenerates after each harvest.

**Positive ecological impact** - It is estimated that the Portuguese cork oak forest - montado - is responsible for retaining 5% of the country's annual CO<sub>2</sub> emission, representing 4.8 million tons per year.

+)

An activity that crosses generations - Cork Oaks are manually harvested for the first time when the tree is 25 years old and then every 9 years making it an activity that passes from generation to generation.

A positive economic and social impact - Cork harvesting is a regular and cyclical process that contributes to environmental, economic and social sustainability of the rural areas in the Mediterranean region.

**Rural areas economic engine** - The cork activity as well as related activities fueled by this industry create jobs in many rural areas of the country, encouraging people to settle there.



# Product Selector

RANGE	G	0	Resist	Resist*	hydre	cork
FINISHING	0,2mm Wear Layer	0,3mm Wear Layer	0,55mm Wear Layer	0,55mm Wear Layer	0,55mm V	Vear Layer
CLASS OF USE (ISO 10874)	23 Residential 31 Commercial	23 Residential 32 Commercial	23 Residential 33 Commercial	23 Residential 33 Commercial		idential Imercial
BEVEL	No E	Bevel	4 Side Micro Bevel	4 Side Micro Bevel	4 Side Mi	cro Bevel
DIMENSION (mm   inches)	<b>1220 x 185</b> 48 x 71/		<b>1220 x 185 x 10,5mm</b> 48 x 7 1/4 x 3/8″	<b>1220 x 185 x 10,5mm</b> 48 x 7 1/4 x 3/8″	<b>1225 x 145 x 6mm</b> 48 7/32 x 5 11/16 x 1/4"	<b>1225 x 195 x 6mm</b> 48 7/32 x 7 11/16 x 1/4"
Alaska Oak		B0Q0003		E1Q0001	B5Q0001	
Amber Cherry		B0Q7003				
Antique Frozen Pine				E1XD001		
Antique Smoked Pine				E1XBOO1		
Antique Washed Pine				E1XC001		
Arcadian Artic Pine						B5WT001
Arcadian Rye Pine			B0P5001		B5P5001	
Arcadian Soya Pine			B0P4001		B5P4001	
Bark Oak		B0V8001				
Bleached Oak				E1XO001		
Blonde Oak	B0N1001					
Brown Rustic Pine				E1W1001		
Brume Oak		B0N8001				
Castle Raffia Oak			B0P0001		B5P0001	
Castle Toast Oak			B0P1001		B5P1001	
Century Fawn Pine			B0P7001		B5P7001	
Century Morocco Pine			B0P6001		B5P6001	
Chalk Oak		B0Q1003		E1Q1001	B5Q1001	
Cinder Oak			B0R7001	E1R7001	B5R7001	
Classic Nature Oak	B0S3001					



RANGE	G	60	Esse	ence	Resist	Resist*	hydre	cork	
FINISHING	0,2mm Wear Layer	0,3mm Wear Layer	NPC		0,55mm Wear Layer	0,55mm Wear Layer	0,55mm Wear Layer		
CLASS OF USE (ISO 10874)	23 Residential 31 Commercial	23 Residential 32 Commercial	23 Res 32 Com	idential Imercial	23 Residential 33 Commercial	23 Residential 33 Commercial		23 Residential 33 Commercial	
BEVEL	No E	Bevel	No Bevel	4 Side Bevel	4 Side Micro Bevel	4 Side Micro Bevel	4 Side Mi	cro Bevel	
DIMENSION (mm   inches)		<b>x 10,5mm</b> /4 x 3/8″	<b>1220 x 185 x 10,5mm</b> 35 5/8 x 11 5/8 ″	<b>1830 x 185 x 11,5mm</b> 72 x 7 1/4 x 1/2"	<b>1220 x 185 x 10,5mm</b> 48 x 7 1/4 x 3/8"	<b>1220 x 185 x 10,5mm</b> 48 x 7 1/4 x 3/8"	<b>1225 x 145 x 6mm</b> 48 7/32 x 5 11/16 x 1/4″	<b>1225 x 195 x 6mm</b> 48 7/32 x 7 11/16 x 1/4	
Classic Prime Oak				D8F4001					
Claw Silver Oak					B0V3001	E1V3001	B5V3001		
Coal Oak				D8F2001					
Country Prime Oak				D8F8001					
Croft Oak		B0V9001							
Dapple Oak				D8F1001					
Dark English Oak						E1XM001			
Dark Grey Washed Oak						E1XJ001			
Dark Red Oak						E1XLOO1			
Elegant Dark Oak						E1XF001			
Elegant Light Oak						E1XG001			
Elegant Oak					B0R4001	E1R4001	B5R4001		
European Nature Oak						E1XEOO1			
European Oak		B0Q2004					B5Q2001		
European Smoked Oak						E1L7001			
Fall Pine	B0S0001								
Frozen Oak		B0N9001				E1N9001			
Glacier Rustic Pine			D822003						
Golden Prime Oak				D8F7001					
Grey Rustic Pine						E1W2001			

# Product Selector

RANGE	c	Go	Esse	ence	Resist	Resist*	hydre	cork	
FINISHING	0,2mm Wear Layer	0,3mm Wear Layer	NPC		0,55mm Wear Layer	0,55mm Wear Layer	0,55mm Wear Layer		
CLASS OF USE (ISO 10874)	23 Residential 31 Commercial	23 Residential 32 Commercial	23 Res 32 Com	idential nmercial	23 Residential 33 Commercial	23 Residential 33 Commercial		23 Residential 33 Commercial	
BEVEL	No I	Bevel	No Bevel	4 Side Bevel	4 Side Micro Bevel	4 Side Micro Bevel	4 Side Mi	cro Bevel	
DIMENSION (mm   inches)		5 <b>x 10,5mm</b> /4 x 3/8″	<b>1220 x 185 x 10,5mm</b> 35 5/8 x 11 5/8 ″	<b>1830 x 185 x 11,5mm</b> 72 x 7 1/4 x 1/2"	1220 x 185 x 10,5mm 48 x 7 1/4 x 3/8"	<b>1220 x 185 x 10,5mm</b> 48 x 7 1/4 x 3/8″	<b>1225 x 145 x 6mm</b> 48 7/32 x 5 11/16 x 1/4″	<b>1225 x 195 x 6mm</b> 48 7/32 x 7 11/16 x 1/4″	
Grey Washed Oak						E1XK001			
Highland Pine	B0S1001								
Indian Dark Oak	B0S5001								
Inspired Pine			D898001						
Ivory Chalk Oak			D887001	D887002					
Ivory Salt Oak	B0N2001								
Light Beech					B0T0002		B5T0001		
Light Dawn Oak								B5WS001	
Light Sucupira		B009001							
Light Washed Oak						E1XIOO1			
Limed Grey Oak					B0T7001	E1T7001	B5T7001		
Limed White Rustic Oak	BOWBOO1								
Linen Cherry					BOROOO1		B5R0001		
Midnight Oak		B0M5001							
Natural Larch	B0W5001								
Nature Oak					B0T5001		B5T5001		
Nature Rustic Pine						E1XA001			
Nebraska Rustic Pine			D885001	D885002					
Nebula Oak				D8F3001					
Nordic Ash					B0V4001				



RANGE	G	io	Esse	ence	Resist	Resist*	hydre	cork	
FINISHING	0,2mm Wear Layer	0,3mm Wear Layer	NPC		0,55mm Wear Layer	0,55mm Wear Layer	0,55mm Wear Layer		
CLASS OF USE (ISO 10874)	23 Residential 31 Commercial	23 Residential 32 Commercial	23 Res 32 Com	idential nmercial	23 Residential 33 Commercial	23 Residential 33 Commercial		23 Residential 33 Commercial	
BEVEL	No E	Bevel	No Bevel	4 Side Bevel	4 Side Micro Bevel	4 Side Micro Bevel	4 Side Mi	cro Bevel	
DIMENSION (mm   inches)	1220 x 185 48 x 7 1/		<b>1220 x 185 x 10,5mm</b> 35 5/8 x 11 5/8 ″	<b>1830 x 185 x 11,5mm</b> 72 x 7 1/4 x 1/2"	1220 x 185 x 10,5mm 48 x 7 1/4 x 3/8″	<b>1220 x 185 x 10,5mm</b> 48 x 7 1/4 x 3/8″	<b>1225 x 145 x 6mm</b> 48 7/32 x 5 11/16 x 1/4″	<b>1225 x 195 x 6mm</b> 48 7/32 x 7 11/16 x 1/4	
Oiled Nature Oak						E1XN001			
Oiled Taupe Oak	BOWA001								
Old Larch	B0W6001								
Platinum Chalk Oak			D886001	D886002					
Platinum Oak		B0M6001							
Polar Nature Oak	B0R9001								
Prime Arctic Oak				D8F6001					
Prime Desert Oak				D8F5001					
Prime European Cherry			D826003						
Prime Rustic Oak			D884002	D884001					
Provence Oak		B0Q3003				E1Q3001			
Quartz Larch	B0W3001								
Rustic Eloquent Oak				D8F9001					
Rustic Fawn Oak								B5WU001	
Rustic Forest Oak				D8G0001					
Rustic Grey Oak								B5WV001	
Rustic Limed Gray Oak					B0U0001				
Rustic Taupe Oak	BOWC001								
Sand Oak					BOR1001	E1R1001	B5R1001		
Savanna Limed Oak	B0N6001								

# Product Selector

RANGE	G	Go	Esse	ence	Resist	Resist*	hydro	cork
FINISHING	0,2mm Wear Layer	0,3mm Wear Layer	NPC		0,55mm Wear Layer	0,55mm Wear Layer	0,55mm \	Wear Layer
CLASS OF USE (ISO 10874)	23 Residential 31 Commercial	23 Residential 32 Commercial	23 Res 32 Com	idential nmercial	23 Residential 33 Commercial	23 Residential 33 Commercial		idential Imercial
BEVEL	No E	Bevel	No Bevel	4 Side Bevel	4 Side Micro Bevel	4 Side Micro Bevel	4 Side M	icro Bevel
DIMENSION (mm   inches)	<b>1220 x 18</b> 5 48 x 7 1/	5 x 10,5mm /4 x 3/8″	<b>1220 x 185 x 10,5mm</b> 35 5/8 x 11 5/8 ″	<b>1830 x 185 x 11,5mm</b> 72 x 7 1/4 x 1/2"	<b>1220 x 185 x 10,5mm</b> 48 x 7 1/4 x 3/8″	<b>1220 x 185 x 10,5mm</b> 48 x 7 1/4 x 3/8″	<b>1225 x 145 x 6mm</b> 48 7/32 x 5 11/16 x 1/4″	<b>1225 x 195 x 6mm</b> 48 7/32 x 7 11/16 x 1/4″
Sawn Bisque Oak					B0P3001		B5P3001	
Sawn Twine Oak					B0P2001		B5P2001	
Shell Oak	B0N4001							
Smoked Rustic Oak					B0U4001	E1U4001		
Sorrel Carve Oak			D838003	D838004				
Storm Oak	B0N3001							
Sylvan Brown Oak								B5WQ001
Sylvan Gold Oak								B5L8001
Washed Arcaine Oak				D8G1001				
Washed Castle Oak				D8G4001				
Washed Haze Oak				D8G2001				
Washed Highland Oak				D8G3001				
Wheat Oak								B5WR001
Wheat Pine					BOR3001		B5R3001	
White Oak		B0M8001						
White Washed Oak						E1XHOO1		



# Wicanders' range





Nature at your feet



#### HeadQuarters

Amorim Revestimentos S.A (+351) 227 475 600 geral.ar@amorim.com

#### www.wicanders.com

DE	Amorim Deutschland GmbH (+49) 4221 5 93-01	germany.ar.de@amorim.com
BE NE LUX	Amorim Benelux B.V. (+31) 166 604 111	info.ar.nl@amorim.com
AT	Amorim Deutschland GmbH (+43) 1 54 51 65 10	austria.ar.de@amorim.com
CH	Amorim Flooring Switzerland AG (+41) 41 726 20 20	info@amorim.ch
PT	Amorim Revestimentos, S.A. (+351) 227 475 600	geral.ar@amorim.com
ES	Amorim Revestimentos, S.A. (+34) 902 307 407	info.ar.es@amorim.com
FR	Amorim Revestimentos, S.A. (+33) 800 914 848	info.ar.fr@amorim.com
DK	Timberman Denmark A/S (+45) 995 252 52	timberman@timberman.dk
PL	Dom Korkowy, Sp. z o.o. (+48) 126 379 639	krakow@domkorkowy.pl
US	Amorim Flooring North America (+1) 410 553 60 62	info.ar.us@amorim.com
RU	Amorim Flooring Rus, OOO (+7) 495 280 7860	info.ar.ru@amorim.com
SW	Amorim Flooring Sweden +46 (0)31107740	order.se@wicanders.com



C<sup>®</sup>MPETE **2020** 





UNIÃO EUROPEIA Fundo Europeu de Desenvolvimento Regional

